

TECHNICAL DATA SHEET

DESCRIPTION

The patented, PC110 Suprotek Impalement Safety Cap is an OSHA approved, safety device used to eliminate impalement of falling workers from a height. It consists of a highly visible, safety orange top over a heavy duty, steel plate.

APPLICATION

The Suprotek Impalement Safety Cap is used to prevent rebar and stakes from impaling a worker, in the event of a fall.

PRODUCT SPECIFICATION

- Safety orange color
- Rated for 250lb drop at 7-1/2 ft.
- Fits rebar sizes #3 [10mm] up to #11 [36mm], flat stakes (3/8" x 1-1/2") and round stakes (5/8" to 7/8")



FEATURES

- Tested and approved by CAL OSHA
- Highly visible, OSHA required lettering
- One cap covers most rebar sizes and popular flat and round stakes

BENEFITS

- Only need to stock one part number
- Usable on any jobsite
- Easily readable OSHA information
- Faster product fulfillment times

APPROVALS / COMPLIANCE

- Cal OSHA 344.90
- Federal OSHA 1926.701(b)
- CAL OSHA Approval Numbers C-1730-AG, C-1716-AG

INSTALLATION

1. Placed onto the end of a protruding rebar, flat or round stake.
2. Apply force onto the cap face until the cap's internal, metal insert contacts the end of the rebar or stake.

RELATED PRODUCTS

- PC200 Suprotek[®] Impalement Safety Cap
- D48 Sure-Guard[®] Rebar Protector

HOW TO ORDER

Specify: (1) quantity, (2) name, (3) bar size
 Example: 500, PC110, #3[10mm]-#11[36mm]

ORDERING INFORMATION

Product Code	Description	Weight
146207	#3 [10MM] - #11 [36MM]	0.37 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.