

Revision date : 2017/12/01 Version: 4.0

Page: 1/10 (30605461/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterProtect P 110

Recommended use of the chemical and restriction on use

Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

<u>Company:</u> BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300 BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No data available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Repr.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity
STOT RE	2	Specific target organ toxicity — repeated
		exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute
Aquatic Chronic	3	Hazardous to the aquatic environment - chronic

Label elements

Revision date : 2017/12/01 Version: 4.0

Pictogram:		
V		
Signal Word: Danger		
Hazard Statement:		
H373	May cause damage to organs (Kidney) through prolonged or repeated exposure.	
H360 H412	May damage fertility. May damage the unborn child. Harmful to aquatic life with long lasting effects.	
H401	Toxic to aquatic life.	
Precautionary Statements (Prevention):		
P280	Wear protective gloves/protective clothing/eye protection/face protection.	
P273 P260	Avoid release to the environment. Do not breathe dust/gas/mist/vapours.	
P200 P201	Obtain special instructions before use.	
P202	Do not handle until all safety precautions have been read and understood.	
Precautionary Statements (Response):		
P314 P308 + P311	Get medical advice/attention if you feel unwell. IF exposed or concerned: Call a POISON CENTER or doctor/physician.	
Precautionary Statements (Storage):		
P405	Store locked up.	
Precautionary Statements (Disposal): P501 Dispose of contents/container to hazardous or special waste collection		
	point.	

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Weight %	Chemical name
84-74-2	>= 1.0 - < 3.0%	dibutyl phthalate
107-21-1	>= 1.0 - < 3.0%	ethylene glycol

4. First-Aid Measures

Description of first aid measures

Safety Data Sheet

MasterProtect P 110 Revision date : 2017/12/01

Version: 4.0

General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media: foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons: water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting: carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Advice for fire-fighters

Protective equipment for fire-fighting: Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do

Revision date : 2017/12/01 Version: 4.0

Page: 4/10 (30605461/SDS_GEN_US/EN)

not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed. For large amounts: Pump off product.

7. Handling and Storage

Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion: Product is not explosive.

Conditions for safe storage, including any incompatibilities Observe VCI storage rules.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, wellventilated place away from ignition sources, heat or flame. Protect from direct sunlight. Protect from temperatures below: 5 °C The packed product must be protected from temperatures below the indicated one. Protect from temperatures below: 40 °F The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls/Personal Protection

Components with occupational exposure limits

dibutyl phthalate	OSHA PEL ACGIH TLV	PEL 5 mg/m3;TWA value 5 mg/m3; TWA value 5 mg/m3;
ethylene glycol	ACGIH TLV	CLV 100 mg/m3 aerosol;

Advice on system design:

No applicable information available.

Revision date : 2017/12/01 Version: 4.0

Personal protective equipment

Respiratory protection:

Wear respiratory protection if ventilation is inadequate.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Safety glasses with side-shields.

Body protection:

light protective clothing

General safety and hygiene measures:

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

9. Physical and Chemical Properties

Form: Odour: Odour threshold: Colour: pH value: Melting temperature: Boiling range: Sublimation point: Flash point: Flash point: Flammability: Flammability of Aerosol Products: Lower explosion limit: Upper explosion limit: Upper explosion limit: Autoignition: Vapour pressure: Density: Relative density: Vapour density: Partitioning coefficient n- octanol/water (log Pow): Self-ignition temperature: Thermal decomposition: Viscosity, dynamic:	liquid sweetish No applicable information available. opaque 4 - 5 The product has not been tested. $182.22 - 340 ^{\circ}\text{C}$ No applicable information available. > 201 °F not determined not applicable, the product does not form flammable aerosoles dropped No applicable information available. Study does not need to be conducted. The product has not been tested. 1.0 - 1.1 g/cm3 $(20 ^{\circ}\text{C})$ No applicable information available. Heavier than air. No applicable information available. not self-igniting No decomposition if stored and handled as prescribed/indicated. 700 - 1,500 mPa.s $(20 ^{\circ}\text{C})$ No applicable information available
Viscosity, dynamic. Viscosity, kinematic: Solubility in water: Solubility (quantitative): Solubility (qualitative): Evaporation rate:	

Safety Data Sheet

MasterProtect P 110 Revision date : 2017/12/01 Version: 4.0

Other Information:

If necessary, information on other physical and chemical parameters is indicated in this section.

Page: 6/10

(30605461/SDS_GEN_US/EN)

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

Conditions to avoid

See MSDS section 7 - Handling and storage.

Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

Hazardous decomposition products

Decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. Based on available Data, the classification criteria are not met. The product has not been tested. The statement has been derived from the properties of the individual components.

Oral

No applicable information available.

Inhalation No applicable information available.

<u>Dermal</u> No applicable information available.

Revision date : 2017/12/01 Version: 4.0

<u>Assessment other acute effects</u> No applicable information available.

Irritation / corrosion

Assessment of irritating effects: No irritation is expected under intended use and appropriate handling. Based on available Data, the classification criteria are not met.

Sensitization

Assessment of sensitization: No applicable information available.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: The substance may cause damage to the kidney after repeated ingestion. The substance may cause damage to the kidney after repeated skin contact with high doses.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Reproductive toxicity

Assessment of reproduction toxicity: Causes impairment of fertility in laboratory animals.

Teratogenicity

Assessment of teratogenicity: The substance caused malformations/developmental toxicity in laboratory animals.

Information on: dibutyl phthalate

Assessment of teratogenicity: The results of animal studies gave indication of a developmental toxic/teratogenic effects with high doses.

Information on: ethylene glycol

Assessment of teratogenicity: Developmental toxicity was observed after oral ingestion of high doses in studies with rats and mice, but this effect was not seen in a study with rabbits. Mechanistic studies show that the rabbit is the relevant species for the classification for human health. As such, and since ethylene glycol is not a developmental toxicant in the rabbit, no classification is warranted. However, the relevance of this result for humans is unclear.

Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

Revision date : 2017/12/01 Version: 4.0

12. Ecological Information

Toxicity

Aquatic toxicity Assessment of aquatic toxicity: Acutely toxic for aquatic organisms. May cause long-term adverse effects in the aquatic environment.

Persistence and degradability

<u>Assessment biodegradation and elimination (H2O)</u> Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

Bioaccumulative potential

<u>Assessment bioaccumulation potential</u> Discharge into the environment must be avoided.

Mobility in soil

Assessment transport between environmental compartments No data available.

Additional information

Other ecotoxicological advice: Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport USDOT

Not classified as a dangerous good under transport regulations

Sea transport IMDG

Not classified as a dangerous good under transport regulations

Revision date : 2017/12/01 Version: 4.0

Page: 9/10 (30605461/SDS_GEN_US/EN)

Air transport

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:ChemicalTSCA, USreleased / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

EPCRA 313:

100 LBS

10 LBS

CAS Number	<u>Chemical name</u>	
84-74-2	dibutyl phthalate	
107-21-1	ethylene glycol	
111-90-0	Ethanol, 2-(2-ethox	yethoxy)-
CERCLA RQ	CAS Number	Chemical name
5000 LBS	107-21-1; 108-05-	ethylene glycol; vinyl acetate
	4	
1000 LBS	75-07-0	acetaldehyde

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including FORMALDEHYDE (GAS), which is known to the State of California to cause cancer, and DI-N-BUTYL PHTHALATE (DBP), which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

Formaldehvde

dibutyl phthalate

[Other Prop 65 components may be present in the product.]

NFPA Hazard codes: Health: 1 Fire: 1 Reactivity: 0 Special:

50-00-0

84-74-2

16. Other Information

SDS Prepared by:

BASF NA Product Regulations SDS Prepared on: 2017/12/01

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Revision date : 2017/12/01 Version: 4.0

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET