

PN: H22312162



• Fall Protection • Competent Training • Netting • PPE

Phone: (504) 733-1808
Fax: (504) 733-2996
PalmerSafetyUS.com

TECHNICAL SPECIFICATIONS

Harness 5pt., QCB, Padded Back & Leg, Side D-Rings, Positioning Belt, Dual Front D Rings.

Black top, black padding, 5 point FBH, QCB all aluminum hardware, padded back sewn in, padded legs sewn in. Positioning belt black. 1 Back D-ring, 2 Hip D-rings, 2 Front D-rings. Multiple sizes. SRL back plate. Meets or Exceeds ANSI Z359.11-2014. A10.32-2012



USER CAPACITY: 130 - 420 lbs.

DESIGN:

- One (1) dorsal attachment D-ring for fall arrest; one (1) front D-ring for climbing purpose; one (1) ventral D-ring for rope access purpose
- Equipped with work positioning belt with two (2) side D-rings for work positioning
- Adjustable shoulder straps for easy adjustment and snug fitting
- Adjustable leg straps for snug fitting
- One (1) lanyard keeper has been incorporated to store unused leg of the lanyard

WEBBING: Material: Polyester | Width: 1.73 in. ± 0.04 in. | Breaking Strength: 5000 lbs.

STITCHING THREAD: Material: High-tenacity polyester

METAL COMPONENT:

Material: All Black Aluminum Hardware

WEIGHT OF HARNESS:

5.82 lbs. ± 0.02 lbs.

Part #	Size
H22312162.S/M	Small - Medium
H22312162.L/XL	Large - X-Large