

TECHNICAL DATA SHEET

DESCRIPTION


B2 coil ties are strong, versatile resistance welded ties designed to take the abuse encountered in medium and heavy concrete construction

APPLICATION

The coil ties can be used as a combination tie and form spreader when it is not necessary to keep the ends of the tie back from the face of the concrete.



With Washers



FEATURES

- It can be used with or without cones
- Can be combined with coil rod to form an adjustable tie
- Available in 1/2", 3/4", 1", 1 1/4" and 1-1/2" diameters in plain or electro galvanized finish

- To determine the required coil tie length, subtract two times the desired or specified setback from the wall thickness
- Safe working load provides a factor of safety of approximately 2 to 1
- Can be used with B4 Water Resistant Washer to break the continuity of the tie to help eliminate water seepage long the tie.

TECHNICAL DATA

SWL provides a factor of safety of approximately 2 to 1.

Type	Bolt Diameter	Number of Strut Wires	Safe Working Load Tension (lbs.)
B2 Standard	1/2"	4	9,000
B2 Heavy	1/2"	4	13,500
B2 Standard	3/4"	4	13,500
B2 Heavy	3/4"	4	18,000
B2 Standard	1"	4	18,000
B2 Heavy	1"	4	27,000
B2 Standard	1-1/4"	4	27,000
B2 Heavy	1-1/4"	4	37,000
B2 Standard	1-1/2"	4	27,000

RELATED PRODUCTS

- B29 Plastic Cone
- B12 Coil Rod
- B14 Coil Bolt
- B11 Flat Washer
- B39 Wing Nuts
- B4 Washer

ORDERING INFORMATION

B2 COIL TIES

Product Code	Description	Weight
124958	1" X 8" PLAIN	1.68 LB
40622	1" X 12" PLAIN	2.50 LB
128069	1" X 12" ELECTRO GALV.	2.55 LB
40704	1-1/4" X 12" PLAIN	3.63 LB
124156	3/4" X 6" PLAIN	1.33 LB
127310	3/4" X 6" ELECTRO GALV.	1.35 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

TECHNICAL DATA SHEET

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.