

TECHNICAL DATA SHEET

DESCRIPTION

The C52 Guardrail Receptacle bolts to Dayton Superiors C49 bridge overhang bracket providing an OSHA approved receptacle for 2x4 guard rail posts.

APPLICATION

The C52 Guardrail Receptacle is designed to allow the easy installation of an OSHA required lumber guard rail post on the exterior framework of a bridgedeck.

PRODUCT SPECIFICATION

- Designed for use with 2x4 lumber posts
- Bolts directly to Dayton Superior C49 Bridge Overhang Brackets and C54 Extenders



C52 Guard Rail Receptacle

FEATURES

- Mounting hardware included
- Compatible with Dayton Superior C48, C49D, C49s, and C49JR Bridge Overhang Brackets and C54 Extender

BENEFITS

- Simple, easy installation
- Facilitates quick assembly of lumber guard rails on exterior formwork

APPROVALS / COMPLIANCE

- OSHA compliant

RELATED PRODUCTS

- C49 Bridge Overhang Bracket
- C53 Guardrail Receptacle
- C54 Bridge Overhang Extender

HOW TO ORDER

- To order:
Specify: (1) quantity, (2) name

Example:
600 Pieces, C52 2x4 Guard Rail receptacle

ORDERING INFORMATION

GUARD RAIL RECEPTACLE

Product Code	Description	Weight
60320	2 X 4 GUARD RAIL RECEPTACLE	3.09 LB

MANUFACTURER

Dayton Superior Corporation
 1125 Byers Road
 Miamisburg, OH 45342
 Customer Service: 888-977-9600
 Technical Services: 877-266-7732
 Website: www.daytonsuperior.com

WARRANTY (ACCESSORIES)

Limited Warranty. Dayton warrants, for a period of 60 days from the date of shipment (three years from the date of shipment in the case of formwork, excluding any consumable Products included with such formwork), that Products and any associated application drawings and engineering services provided by Dayton ("Ancillary Services") will be free from defects in material and workmanship and, in the case of custom designed formwork, that the formwork will meet the specifications set forth in the design drawings approved by Dayton and Customer. Any claim under this warranty must be made in writing within such warranty period. If any Product and/or Ancillary Service covered by a timely claim are found to be defective, Dayton will, within a reasonable time, make any necessary repairs or corrections or, at Dayton's option, replace the Product. Unless pre-authorized by Dayton in writing, Dayton will not accept any charges for correcting defects or accept the return of any Product. This warranty will not apply to any Products that have been subjected to misuse, neglect, storage damage, misapplication, accident or any other damage caused by any person other than Dayton, or that have not been maintained in accordance with Dayton's specifications. THIS LIMITED WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES AS TO THE PRODUCTS AND ANCILLARY SERVICES. DAYTON MAKES NO OTHER WARRANTIES OR GUARANTEES, EXPRESS OR IMPLIED, INCLUDING ANY WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR OTHERWISE. THE REMEDIES SET FORTH IN THIS SECTION ARE CUSTOMER'S EXCLUSIVE REMEDY FOR BREACH OF WARRANTY.