1 Identification of the substance and manufacturer		
Trade name:	ORANGE FLUORESCENT	
Product code: Recommended use: Uses advised against: Manufacturer/Supplier: Emergency telephone number:	0000200957 Paint and coatings application. Any that differs from the recommended use. Seymour of Sycamore 917 Crosby Avenue Sycamore, IL 60178 USA phone: 815-895-9101 www.seymourpaint.com 1-800-255-3924	Seymour of Sycamore 3041 Dougall Avenue, Suite 503 Windsor, ONT N9E 1S3 CANADA phone: 800-435-4482 www.seymourpaint.com
2 Hazard(s) identification		
Classification of the substance or mixture Flam. Aerosol 1 H222 Extremely flammable aerosol. Press. Gas H280 Contains gas under pressure; may explode if heated. STOT SE 3 H335 May cause respiratory irritation. STOT RE 2 H373 May cause damage to organs through prolonged or repeated exposure. GHS Hazard pictograms GHS02 GHS04 GHS07 GHS08		
Signal word Hazard statements	Danger Extremely flammable aerosol. Contains gas under pressure; may explode if heated. May cause respiratory irritation. May cause damage to organs through prolonged or rep	peated exposure.
Precautionary statements	Keep away from heat/sparks/open flames/hot surfaces Do not spray on an open flame or other ignition source Pressurized container: Do not pierce or burn, even afte Do not breathe dust/fume/gas/mist/vapors/spray. Use only outdoors or in a well-ventilated area. IF INHALED: Remove person to fresh air and keep con Call a poison center/doctor if you feel unwell. Store in a well-ventilated place. Store locked up. Protect from sunlight. Do not expose to temperatures e Dispose of contents/container in accordance with local	a No smoking. er use. mfortable for breathing. exceeding 50°C/122°F.

	3 Composition/information on ingredients		
	l characterization: Mixtures I Description:	<b>s</b> This product is a mixture of the substances listed below with nonhazardous additions.	
	us components:		
	-3 Calcium Carbonate		
	-6 propane		
	-8 VM&P Naphtha		
	-8 n-butane		
	-8 Mineral Spirits		
	-5 heptane		
110-19	-0 Isobutyl Acetate		

4 First-aid measures	
After inhalation: After skin contact: After eye contact: After swallowing: Most important symptoms and effects: Indication of any immediate medical attention needed:	Supply fresh air; consult doctor in case of complaints. Remove contaminated clothing. Wash exposed area with soap and water. Rinse opened eye for several minutes under running water. Then consult a doctor. Rinse mouth with water. Do not induce vomiting. Dizziness No further relevant information available.
E Fire fighting managemen	
5 Fire-fighting measures	
Extinguishing agents: Special hazards: Protective equipment for firefighters:	CO2, extinguishing powder or water spray. Fight larger fires with water spray. Can form explosive gas-air mixtures. A respiratory protective device may be necessary.

25-50% 15-25% 10-15% 5-10% 5-10%

≥5-<10% 5-10% Trade name: ORANGE FLUORESCENT

Page 2/4

Trade Hame: ORANGE FLUORESCENT			
	(Contd. of page 1)		
6 Assidental release measures			
6 Accidental release measures Personal precautions, protective			
equipment and emergency			
procedures:	Use respiratory protective device against the effects of fumes/dust/aerosol.		
Methods and material for containment and cleaning up:	Absorb liquid components with liquid-binding material.		
7 Handling and storage			
Precautions for safe handling	Use only in well ventilated areas.		
Storage requirements:	Keep away from sources of heat and direct sunlight. Do not warehouse in subfreezing conditions.		
	Store locked up.		
8 Exposure controls/personal prot			
	require monitoring at the workplace:		
74-98-6 propane PEL (USA)   Long-term value: 1800 mg	a/m³ 1000 ppm		
REL (USA) Long-term value: 1800 mg			
TLV (USA) refer to Appendix F inTLV			
106-97-8 n-butane			
REL (USA) Long-term value: 1900 mg			
TLV (USA) Short-term value: 2370 m (EX)	g/m³, 1000 ppm		
142-82-5 heptane			
PEL (USA) Long-term value: 2000 mg	g/m <sup>3</sup> , 500 ppm		
REL (USA) Long-term value: 350 mg/	/m <sup>3</sup> . 85 ppm		
Ceiling limit value: 1800*	mg/m³, 440* ppm		
*15-min TLV (USA) Short-term value: 2050 m	a/m <sup>3</sup> 500 ppm		
Long-term value: 1640 mg	Long-term value: 1640 mg/m <sup>3</sup> , 400 ppm		
110-19-0 Isobutyl Acetate			
PEL (USA) Long-term value: 700 mg/			
REL (USA) Long-term value: 700 mg/			
TLV (USA) Short-term value: 712 mg. Long-term value: 238 mg/	/m³, 150 ppm /m³ 50 ppm		
Hygienic protection:	Immediately remove all soiled and contaminated clothing.		
	Wash hands after use.		
Breathing equipment:	Do not eat or drink while working. A respirator is generally not necessary when using this product outdoors or in large open areas. In		
Dicating equipment.	cases where short and/or long term overexposure exists, a charcoal filter respirator should be worn.		
lland avatastica.	If you suspect overexposure conditions exist, please consult an authority on chemical hygeine.		
Hand protection:	Nitrile gloves. The glove material must be impermeable and resistant to the substance.		
Eye protection:	Tightly sealed goggles		
9 Physical and chemical propertie			
Appearance: Odor:	Aerosol. Aromatic		
Odor: Odor threshold:	Not determined.		
pH-value:	Not determined.		
Melting point/Melting range	Undetermined.		
Boiling point:	-44 °C (-111.2 °F)		
Flash point:	-19 °C (-66.2 °F)		
Flammability (solid, gas):	Extremely flammable.		
Decomposition temperature:	Not determined.		
Auto igniting:	Product is not self-igniting.		
Danger of explosion: Lower Explosion Limit:	In use, may form flammable/explosive vapour-air mixture. 1.7 Vol %		
Upper Explosion Limit:	10.9 Vol %		
Vapor pressure:	Not determined.		
Relative Density:	Between 0.77 and 0.85 (Water equals 1.00)		
Vapor density	Not determined.		
Evaporation rate Partition coefficient: n-octonal/wate	Not applicable. er: Not determined		
	(Contd. on page 3)		

Trade name: ORANGE FLUORESCENT

Page 3/4 Page 3/4		
nting date 01/10/2020	Revised On 01/06/2020	
ade name: ORANGE FLUORESCENT		
	(Contd. of page 2)	
Solubility: Viscosity: VOC content (less exempt solvents)	Not determined. Not determined. : 56.9 %	
0 Stability and reactivity		
Reactivity: Conditions to avoid:	Stable at normal temperatures. Do not allow can to exceed 120 degrees Fahrenheit. Do not warehouse in subfreezing temperatures.	
Chemical stability: Possibility of hazardous reactions: Incompatible materials: Hazardous decomposition:	Not fully evaluated. No dangerous reactions known. No further relevant information available. No dangerous decomposition products known.	

	11	l Tox	icolog	ical inf	format	ion
--	----	-------	--------	----------	--------	-----

LD/LC50	alues tha	t are relevant for	lassification:
106-97-8 r	n-butane		
Inhalative	LC50/4 h	658 mg/l (rat)	
110-19-0 I	sobutyl A	cetate	
Oral	LD50	4,763 mg/kg (rbt)	
Information on toxicological effects:No data available.Skin effects:No irritant effect.Eye effects:No irritating effect.Sensitization:No sensitizing effects known.			
12 Ecologic	alinform	ation	

Aquatic toxicity:	Hazardous for water, do not empty into drains.
Persistence and degradability:	The product is degradable after prolonged exposure to natural weathering processes.
Other information:	This product does not contain any chlorofluorocarbons (CFC's), hydrochlorofluorocarbons (HCFC's), perfluorocarbons (PFC's), heavy metals (chromium, lead, cadmium), or chlorinated solvents.
Bioaccumulative potential:	No further relevant information available.
Mobility in soil:	No further relevant information available.
Ecotoxícal effects:	
Remark:	Toxic for fish
Other adverse effects:	No further relevant information available.

## **13 Disposal considerations**

Dispose of in accordance with local, state, and federal regulations. Do not puncture, incinerate, or compact. Partially empty cans must be disposed of responsibly. Do not heat or cut empty containers with electric or gas torches. **Recommendation:** Completely empty cans should be recycled.

14 Transport information	
UN-Number DOT DOT	UN1950 N/A Consumer Commodity ORM-D Aerosols, flammable
ADR Transport hazard class(es): Class Marine pollutant: Special precautions for user: EMS Number: Packaging Group: UN "Model Regulation":	1950 Aerosols, ENVIRONMENTALLY HAZARDOUS 2.1 Symbol (fish and tree) Warning: Gases F-D,S-U  UN 1950 AEROSOLS, 2.1, ENVIRONMENTALLY HAZARDOUS

## **15 Regulatory information**

SARA Section 355 (extremely hazardous substances):		
None of the ingredients in this produce	t are listed.	
SARA Section 313 (Specific toxic chemical listings):		
None of the ingredients is listed.		
Toxic Substances Control Act (TSCA): Canadian Domestic Substances Li (DSL):	All hazardous ingredients are found on the inventory list of substances. st All ingredients are listed or exempted.	(Contd. on page 4)

F

Revised On 01/06/2020

	(Contd. of page 3)
Consumer Product Safety Comission (CPSC):	This product complies with 16 CFR 1303 and does not contain more than 90 ppm of lead.
California Proposition 65 chemic	als known to cause cancer:
100-41-4 ethyl benzene	
Prop 65 chemicals known to cause	se birth defects or reproductive harm:
None of the ingredients is listed.	
EPA:	
142-82-5 heptane	D
110-19-0 Isobutyl Acetate	D
16 Other information	
Contact:	Regulatory Affairs