

Revision date : 2019/05/21 Version: 7.0

Page: 1/11 (30605525/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

MasterFlow 713

Recommended use of the chemical and restriction on use

Recommended use*: Product for construction chemicals Recommended use*: for industrial and professional users

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

<u>Company:</u> BASF CORPORATION 100 Park Avenue Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

Emergency telephone number

CHEMTREC: 1-800-424-9300 BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: No applicable information available.

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Carc.	1A (by inhalation)	Carcinogenicity
STOT SE	3 (irritating to respiratory system)	Specific target organ toxicity — single exposure
STOT RE	2 (by inhalation)	Specific target organ toxicity — repeated exposure

Safety Data Sheet Mootor Flow 712

wast	err	IOW	/13
Davialan	مدمام	. 0040	

Revision date : 2019/05/21 Version: 7.0

STOT RE

Page: 2/11 (30605525/SDS_GEN_US/EN)

1 (by inhalation)

Specific target organ toxicity - repeated exposure

Label elements



Signal Word: Danger

Hazard Statement:			
H318	Causes serious eye damage.		
H315	Causes skin irritation.		
H335	May cause respiratory irritation.		
H350	May cause cancer by inhalation.		
H373	May cause damage to organs (Kidney, Immune system) through prolonged or repeated exposure (inhalation).		
H372	Causes damage to organs (lung) through prolonged or repeated exposure (inhalation).		
Precautionary Statemen	ts (Prevention):		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		
P201	Obtain special instructions before use.		
P271	Use only outdoors or in a well-ventilated area.		
P260	Do not breathe dust/gas/mist/vapours.		
P202	Do not handle until all safety precautions have been read and understood.		
P270	Do not eat, drink or smoke when using this product.		
P264	Wash with plenty of water and soap thoroughly after handling.		
Precautionary Statements (Response):			
P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P310	Immediately call a POISON CENTER or doctor/physician.		
P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.		
P303 + P352	IF ON SKIN (or hair): Wash with plenty of soap and water.		
P362 + P364	Take off contaminated clothing and wash it before reuse.		
Precautionary Statements (Storage):			
P403 + P233 P405	Store in a well-ventilated place. Keep container tightly closed. Store locked up.		
Precautionary Statements (Disposal):			
P501	Dispose of contents/container to hazardous or special waste collection point.		

Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

Labeling of special preparations (GHS):

Revision date : 2019/05/21 Version: 7.0 Page: 3/11 (30605525/SDS GEN US/EN)

In combination with water, repeated or prolonged dermal exposure can cause moderate to severe alkali burns.

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

CAS Number	Weight %	<u>Chemical name</u>
65997-15-1	>= 25.0 - < 50.0%	Cement, portland, chemicals
14808-60-7	>= 10.0 - < 15.0%	crystalline silica
1305-78-8	>= 1.0 - < 3.0%	calcium oxide
112945-52-5	>= 1.0 - < 3.0%	Silica

4. First-Aid Measures

Description of first aid measures

General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

If inhaled:

Keep patient calm, remove to fresh air, seek medical attention. Immediately administer a corticosteroid from a controlled/metered dose inhaler.

If on skin:

Immediately wash thoroughly with plenty of water, apply sterile dressings, consult a skin specialist.

If in eyes:

Immediately wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11. Hazards: No applicable information available.

Indication of any immediate medical attention and special treatment needed

 Note to physician
 Treatment:
 Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Revision date : 2019/05/21 Version: 7.0

Suitable extinguishing media: foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons: water jet

Additional information:

Product itself is non-combustible. Only the packaging materials can catch fire. The extinguishing agents normally used are sufficient.

Special hazards arising from the substance or mixture

Hazards during fire-fighting: carbon monoxide, carbon dioxide, harmful vapours Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire. Product is not combustible or explosive.

Advice for fire-fighters

Protective equipment for fire-fighting: Wear self-contained breathing apparatus and chemical-protective clothing.

Further information:

Product itself is non-combustible; fire extinguishing method of surrounding areas must be considered. The degree of risk is governed by the burning substance and the fire conditions. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid dust formation. Avoid contact with skin and eyes. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

For small amounts: Pick up with suitable appliance and dispose of.

For large amounts: Pick up with suitable appliance and dispose of. Pack in tightly closed containers for disposal.

For residues: Rinse with plenty of water. Avoid raising dust.

7. Handling and Storage

Precautions for safe handling

Avoid dust formation. The Cement contained in this product reacts alkaline when in contact with water or humidity. This may cause severe irritation of skin or mucous membranes. The humidity of the skin or mucous membranes is enough for this reaction. Prolonged direct contact to the dry product should be avoided therefore. Avoid inhalation of dusts. Avoid skin contact. Pour downwind and allow as little free fall as possible while emptying bags into equipment. Breathing must be protected when large quantities are decanted without local exhaust ventilation.

Protection against fire and explosion: No special precautions necessary.

Revision date : 2019/05/21 Version: 7.0

Page: 5/11 (30605525/SDS_GEN_US/EN)

Conditions for safe storage, including any incompatibilities

Segregate from metals. Segregate from acids. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Suitable materials for containers: Paper/Fibreboard

Further information on storage conditions: Containers should be stored tightly sealed in a dry place.

8. Exposure Controls/Personal Protection

calcium oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m3;TWA value 5 mg/m3; TWA value 2 mg/m3;
Cement, portland, chemicals	OSHA PEL	PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ; TWA value 10 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ; TWA value 50 millions of particles per cubic foot of air ;
	ACGIH TLV	TWA value 1 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Silica	OSHA PEL	TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, 80mg/m3)/(%SiO2), using a value of 100% SiO2. Lower percentages of SiO2 will yield higher exposure limits. TWA value 20 millions of particles per cubic foot of air ;
Quartz (SiO2)	OSHA PEL	TWA value 0.05 mg/m3 (Respirable dust); OSHA Action level 0.025 mg/m3 (Respirable dust);
	ACGIH TLV	TWA value 0.025 mg/m3 Respirable fraction;

Components with occupational exposure limits

Advice on system design:

Provide local exhaust ventilation to maintain recommended P.E.L.

Personal protective equipment

Respiratory protection:

Breathing protection if dusts are formed.

Hand protection:

Chemical resistant protective gloves, Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

Revision date : 2019/05/21 Version: 7.0

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. Avoid inhalation of dusts. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks). Remove contaminated clothing immediately and clean before re-use or dispose it if necessary.

9. Physical and Chemical Properties

Form: Odour: Odour threshold: Colour: pH value:	powder mild Not determined due to potential health hazard by inhalation. grey 13 (20 °C) (as aqueous solution)
Melting point: Boiling point: Sublimation point: Flash point:	No applicable information available. No applicable information available. No applicable information available. The substance/product is non- combustible.
Flammability: Lower explosion limit:	not determined As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Upper explosion limit:	As a result of our experience with this product and our knowledge of its composition we do not expect any hazard as long as the product is used appropriately and in accordance with the intended use.
Autoignition: Vapour pressure: Relative density: Bulk density: Vapour density: Partitioning coefficient n- octanol/water (log Pow):	No applicable information available. No applicable information available. No applicable information available. 1,200 - 1,800 kg/m3 No applicable information available. No applicable information available.
Self-ignition temperature: Thermal decomposition:	not self-igniting No decomposition if stored and handled as prescribed/indicated.
Viscosity, dynamic: Viscosity, kinematic: Solubility in water: Solubility (quantitative): Solubility (qualitative): Molar mass: Evaporation rate:	No applicable information available. No applicable information available. insoluble No applicable information available. No applicable information available. No applicable information available. No applicable information available.

Safety Data Sheet

MasterFlow 713 Revision date : 2019/05/21

Version: 7.0

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties: Based on its structural properties the product is not classified as oxidizing.

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated. Strong bases are formed on the addition of water.

Conditions to avoid

Avoid dust formation. Avoid humidity.

Incompatible materials

strong bases, strong acids

Hazardous decomposition products

Decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition: No decomposition if stored and handled as prescribed/indicated.

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Virtually nontoxic after a single skin contact. Virtually nontoxic by inhalation. The product has not been tested. The statement has been derived from the properties of the individual components.

<u>Oral</u> No applicable information available.

Inhalation No applicable information available.

<u>Dermal</u> No applicable information available.

<u>Assessment other acute effects</u> Assessment of STOT single: Causes temporary irritation of the respiratory tract.

Revision date : 2019/05/21 Version: 7.0

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Sensitization

Assessment of sensitization: There is no evidence of a skin-sensitizing potential. The product has not been tested. The statement has been derived from the properties of the individual components. Chromate in this product has been reduced. Sensitization due to chromate within stated shelf-live is unlikely.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated exposure may affect certain organs. This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Carcinogenicity

Assessment of carcinogenicity: May cause cancer.

Information on: crystalline silica

Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosolsis classified by the German MAK commision as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.

NTP listed carcinogen

OSHA (Occupational Safety and Health Administration) has classified this substance as carcinogenic.

Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Symptoms of Exposure

Revision date : 2019/05/21 Version: 7.0

Page: 9/11 (30605525/SDS GEN US/EN)

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

12. Ecological Information

Toxicity

Aquatic toxicity Assessment of aquatic toxicity: There is a high probability that the product is not acutely harmful to aquatic organisms. The product gives rise to pH shifts. Based on available Data, the classification criteria are not met.

Persistence and degradability

Assessment biodegradation and elimination (H2O)

Inorganic product which cannot be eliminated from water by biological purification processes. The product is slightly soluble in water. It can be largely eliminated from the water by abiotic processes, e.g. mechanical separation.

Experience shows this product to be inert and non-degradable.

Elimination information

not determined

Bioaccumulative potential

<u>Assessment bioaccumulation potential</u> The product will not be readily bioavailable due to its consistency and insolubility in water.

Mobility in soil

Assessment transport between environmental compartments

The substance will not evaporate into the atmosphere from the water surface. Following exposure to soil, adsorption to solid soil particles is probable, therefore contamination of groundwater is not expected.

Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with local authority regulations. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Completely emptied packagings can be given for recycling.

Revision date : 2019/05/21 Version: 7.0

14. Transport Information

Land transport USDOT	
	Not classified as a dangerous good under transport regulations
Sea transport IMDG	
	Not classified as a dangerous good under transport regulations
Air transport IATA/ICAO	

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status: Chemical TSCA, US released / listed

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations		
State RTK	CAS Number	Chemical name
NJ	1305-78-8	calcium oxide
	65997-15-1	Cement, portland, chemicals
	14808-60-7	Quartz (SiO2)
PA	1305-78-8	calcium oxide
	14808-60-7	crystalline silica
	65997-15-1	Cement, portland, chemicals
	112945-52-5	Silica
	14808-60-7	Quartz (SiO2)

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including SILICA, CRYSTALLINE (AIRBORNE PARTICLES OF RESPIRABLE SIZE), which is known to the State of California to cause cancer. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 0 Reactivity: 0 Special:

16. Other Information

SDS Prepared by: BASF NA Product Regulations

Revision date : 2019/05/21 Version: 7.0

SDS Prepared on: 2019/05/21

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. END OF DATA SHEET